



NOTES:
 A: DRYWALL OR PARGING (BY OTHERS)AS REQ'D.
 C: SEE DATASHEET OF THE INSTALLATION DRAWING FOR LANDING ENTRANCE SCHEDULE.
 D: ALL INFORMATION IS SUBJECT TO CHANGE.

GENERAL SPECIFICATIONS:
 - EACH LANDING ENTRANCE SHALL BE SUPPLIED AS A FINISHED ASSEMBLY WITH DOOR AND FRAME BLANKED, REINFORCED, DRILLED AND TAPPED FOR ALL COMPONENTS DETAILED, READY FOR INSTALLATION.
 - FRAMES SHALL BE WOOD CONSTRUCTION WITH ALL EDGES AND JOINTS SANDED TO A SMOOTH, UNIFORM FINISH, SUPPLIED WITH HARDWARE TO SUIT WOOD WALL CONSTRUCTION.
 - DOORS SHALL BE HOLLOW-CORE, 1 7/8" THICK, SWINGING, FLUSH WOOD CONSTRUCTION COMPLETE WITH (OPTIONAL) GLASS LITE(S) AS INDICATED.
 - OPERATOR HOUSING TO BE FABRICATED FROM ZINC W/PE OPAATED GALVANIZED STEEL WITH ZINC RICH PRIMER, FACTORY APPLIED TOUCH-UP AT THOSE AREA WHERE COATING HAS BEEN REMOVED DUE TO WELDING/GRINDING.

HARDWARE:
 3 SETS OF CONCORD S/S HINGES
 3 PULL HANDLE: 6.687"x1" [170 mm x 75 mm]
 CLOSER/OPENER: CONCORD PRD AUTO III
 KICKPLATE: CON CAB-SIDE OF DOOR: 8" x 35" [203 mm x 889 mm]
 LOCK ASSY: N/A

FINISH
 N/A
 ALUM N/A
 N/A
 #4 S/S
 N/A

OFFICE USE ONLY:
 Part No. _____
 Variant No. _____
 CONFIGURATION VERSION STAMP: _____
 MODULE VERSION STAMP: _____

CUSTOMER: _____
PROJECT: _____
ADDRESS: _____

DATE: MM/DD/YY
 REVISION DATE: MM/DD/YY
 COMPLETED BY: _____

SAVARIA CONCORD
 Your Accessibility Partners

JOB No. _____
 JOB NUMBER 1 OF 1

SHEET No. _____

WOODEN AUTO RH DOOR