



NOTES:

A: DRYWALL OR PARGING (BY OTHERS)AS REQ'D.

C: SEE DATASHEET OF THE INSTALLATION DRAWING FOR LANDING ENTRANCE SCHEDULE.

D: ALL INFORMATION IS SUBJECT TO CHANGE.

GENERAL SPECIFICATIONS:

- EACH LANDING ENTRANCE SHALL BE SUPPLIED AS A FINISHED ASSEMBLY WITH DOOR AND FRAME BLANKED, REINFORCED, DRILLED AND TAPPED FOR ALL COMPONENTS DETAILED, READY FOR INSTALLATION.
- FRAMES SHALL BE WOOD CONSTRUCTION WITH ALL EDGES AND JOINTS SANDED TO A SMOOTH, UNIFORM FINISH, SUPPLIED WITH HARDWARE TO SUIT WOOD WALL CONSTRUCTION.
- DOORS SHALL BE HOLLOW-CORE, 1 7/8" THICK, SWINGING, FLUSH WOOD CONSTRUCTION COMPLETE WITH (OPTIONAL) GLASS LITE(S) AS INDICATED.

HARDWARE:

3 SETS OF CONCORD S/S HINGES

PULL HANDLE: 6687"x1" [170 mm x 75 mm]

CLOSER/OPENER: CONCORD PRD AUTO III

KICKPLATE: CON CAB-SIDE OF DOOR 8" x 35" [203 mm x 889 mm]

LOCK ASSY: N/A

FINISH:

N/A

ALUM

N/A

#4 S/S

OFFICE USE ONLY:

Part No. _____

Variant No. _____

DATE: MM/DD/YY _____

REVISION DATE: MM/DD/YY _____

COMPLETED BY: _____

CUSTOMER: _____

PROJECT: _____

ADDRESS: _____

SAVARIA CONCORD

Your Accessibility Partners

JOB NO. _____

JOB NUMBER 1 OF 1

SHEET NO. _____

WOODEN MANUAL LH DOOR